

XPF-3000

XTREME PRESSURE FILTER

SPECIFICATIONS:

Connection: 1/4" FNPT Inlet and Outlet

Size: O.D. 3.0"

Length: 7.5"

MAOP: 10,000 Psig

Flow: 3.0 GPM @ 100 Psig

Materials: All 316 ss Construction

Element: 100 Mesh or 25 Micron

FEATURES:

Large Capacity Bowl

Welded Reinforced Element Construction

Viton® and Teflon® Seals

Cleanable or Replaceable Element

MADE IN THE USA



 DesignTech INC.

DESIGNING SOLUTIONS FOR TECHNICAL APPLICATIONS

XPF-3000

XTREME PRESSURE FILTER

INFORMATION:

Designed to meet and exceed the demands of today's industrial applications. Constructed completely of 316 ss., it can withstand a wide variety of harsh environments and applications. In addition to chemical resistance the HPF-3000 has also been specifically designed for applications that demand ease in serviceability, long life, and pressures ranging from 0-10,000 psi.

DESIGN ADVANTAGES:

Filter Element:

- Easily Removable
- Cleanable
- Replaceable
- Self Centering
- All 316 ss

Canister:

- Inline Mounting Design
- Wrench Flats for Inline Servicing
- High Pressure Rating
- All 316 ss



DESIGNING SOLUTIONS FOR TECHNICAL APPLICATIONS